

SAFETY DATA SHEET EPOCAST 36®, Basis Mass

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name EPOCAST 36®, Basis Mass

Product number 10016/10026/10036

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Resin.

Uses advised against No specific uses advised against are identified.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers

Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82 353(61)771500 353(61)471285 mail@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

Pictogram





Signal word Warning

Hazard statements H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

EPOCAST 36®, Basis Mass

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P332+P313 If skin irritation occurs: Get medical advice/ attention.

P501 Dispose of contents/ container in accordance with national regulations.

Contains EPOXY RESIN (Number average MW <= 700)

Supplementary precautionary

P261 Avoid breathing vapour/ spray.

statements

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace.

P302+P352 IF ON SKIN: Wash with plenty of water. P321 Specific treatment (see medical advice on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P337+P313 If eye irritation persists: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

QUARTZ 30-60%

Classification
Not Classified

EPOXY RESIN (Number average MW <= 700)

30-60%

CAS number: 25068-38-6 EC number: 500-033-5 REACH registration number: 01-

2119456619-26-0000

Classification

Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Remove affected person from source of contamination.

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion DO NOT induce vomiting. Get medical attention immediately. Rinse mouth thoroughly with

water. Give plenty of water to drink.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. Get medical

attention if irritation persists after washing.

EPOCAST 36®, Basis Mass

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation No specific symptoms known.

Ingestion May cause discomfort if swallowed.

Skin contact Skin irritation. Allergic rash.

Eye contact Irritation of eyes and mucous membranes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctorTreat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion

products

Not known. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen.

5.3. Advice for firefighters

Protective actions during

firefighting

Contain and collect extinguishing water. If risk of water pollution occurs, notify appropriate

authorities.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. In case of spills,

beware of slippery floors and surfaces.

6.2. Environmental precautions

Environmental precautions Avoid discharge into drains or watercourses or onto the ground. Contain spillage with sand,

earth or other suitable non-combustible material.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Absorb in vermiculite, dry sand or earth and place into containers. Collect and place in

suitable waste disposal containers and seal securely. For waste disposal, see Section 13.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. Collect and dispose of spillage as indicated in Section

13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

EPOCAST 36®, Basis Mass

Usage precautions Read and follow manufacturer's recommendations. Do not eat, drink or smoke when using the

product. Contaminated clothing and shoes must be discarded. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the

body with soap and water before leaving the work site.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container. Keep container dry. Keep container tightly closed.

Avoid contact with oxidising agents. Keep away from food, drink and animal feeding stuffs. Do

not store near heat sources or expose to high temperatures.

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

QUARTZ

Long-term exposure limit (8-hour TWA): 0.3 mg/m³

EPOXY RESIN (Number average MW <= 700) (CAS: 25068-38-6)

DNEL Workers - Dermal; Short term systemic effects: 8.33 mg/kg/day

Workers - Inhalation; Short term systemic effects: 12.25 mg/m³

8.2. Exposure controls

Protective equipment





Appropriate engineering controls

Provide adequate ventilation.

Hand protection Butyl rubber. (EN 374) Barrier cream applied before work may make it easier to clean the skin

after exposure, but does not prevent absorption through the skin. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide

information about the breakthrough time of the glove material.

Other skin and body

protection

Use barrier creams to prevent skin contact. Wear appropriate clothing to prevent any

possibility of skin contact.

Respiratory protection Respiratory protection must be used if the airborne contamination exceeds the recommended

occupational exposure limit.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Brown.

Odour Characteristic.

pH Not applicable. Not applicable.

Melting point Not determined.

EPOCAST 36®, Basis Mass

Initial boiling point and range Not applicable.

Evaporation rate Not applicable.

Upper/lower flammability or

explosive limits

Not applicable.

Vapour pressure Not determined.

Vapour density Not applicable.

Relative density Not determined.

Bulk density Not applicable.

Solubility(ies) Immiscible with water.

Auto-ignition temperature Not applicable.

Viscosity Not applicable.

Oxidising properties Does not meet the criteria for classification as oxidising.

9.2. Other information

Other information None.

Volatile organic compound This product contains a maximum VOC content of 0 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Oxidising materials. Acids. Strong alkalis.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

Not relevant.

reactions

10.4. Conditions to avoid

Conditions to avoid Avoid contact with strong oxidising agents. Avoid contact with acids and alkalis.

10.5. Incompatible materials

Materials to avoid Strong oxides.

10.6. Hazardous decomposition products

Hazardous decomposition

No known hazardous decomposition products.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No data recorded.

InhalationNo specific health hazards known.IngestionMay cause discomfort if swallowed.

Skin contact Irritating to skin. May cause sensitisation by skin contact.

EPOCAST 36®, Basis Mass

Eye contact Irritation of eyes and mucous membranes.

Acute and chronic health

The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive

individuals.

SECTION 12: Ecological Information

EcotoxicityThe product contains substances which are toxic to aquatic organisms and which may cause

long-term adverse effects in the aquatic environment.

12.1. Toxicity

hazards

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility The product has poor water-solubility.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in

accordance with the requirements of the local Waste Disposal Authority.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority. Residues and empty containers should be taken care of as

hazardous waste according to local and national provisions.

Waste class 08 04 09

SECTION 14: Transport information

14.1. UN number

 UN No. (ADR/RID)
 3082

 UN No. (IMDG)
 3082

UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy

Resin

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy

Resin)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy

Resin)

EPOCAST 36®, Basis Mass

Proper shipping name (ADN) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A Epoxy

Resin)

14.3. Transport hazard class(es)

ADR/RID class 9

ADR/RID label 9

IMDG class 9

ICAO class/division 9

Transport labels



14.4. Packing group

ADR/RID packing group III

IMDG packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A, S-F

Emergency Action Code •3Z

Hazard Identification Number 90

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (SI 2009

No. 716).

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision date 04/04/2018

Revision 4

EPOCAST 36®, Basis Mass

Supersedes date 06/12/2017

Hazard statements in full H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.