

SAFETY DATA SHEET CHOCKFAST BLACK HARDENER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name CHOCKFAST BLACK HARDENER

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Hardener.

1.3. Details of the supplier of the safety data sheet

Supplier

ITW Performance Polymers

Bay 150

Shannon Industrial Estate

Co. Clare Ireland V14 DF82 353(61)771500 353(61)471285 mail@itwpp.com

1.4. Emergency telephone number

Emergency telephone +44(0)1235 239 670 (24h)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H312 Skin Corr. 1A - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

2.2. Label elements

Pictogram





Signal word Danger

Hazard statements H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Revision date: 05/04/2018 Revision: 5 Supersedes date: 03/05/2016

CHOCKFAST BLACK HARDENER

Precautionary statements P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.

Contains TRIETHYLENETETRAMINE, m-XYLYLENEDIAMINE

Supplementary precautionary

statements

P260 Do not breathe vapour/ spray. P261 Avoid breathing vapour/ spray.

P264 Wash contaminated skin thoroughly after handling.

P272 Contaminated work clothing should not be allowed out of the workplace. P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.
P310 Immediately call a POISON CENTER/ doctor.
P312 Call a POISON CENTER/ doctor if you feel unwell.
P321 Specific treatment (see medical advice on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

TRIETHYLENETETRAMINE 60-100%

CAS number: 112-24-3 EC number: 203-950-6 REACH registration number: 01-

2119487919-13-0000

Classification

Acute Tox. 4 - H312 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412

m-XYLYLENEDIAMINE 10-30%

CAS number: 1477-55-0 EC number: 216-032-5 REACH registration number: 01-

2119480150-50-0000

Classification

Acute Tox. 4 - H302 Acute Tox. 4 - H332 Skin Corr. 1A - H314 Eye Dam. 1 - H318 Skin Sens. 1 - H317 Aquatic Chronic 3 - H412

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation Move affected person to fresh air at once. Get medical attention if any discomfort continues.

Ingestion DO NOT induce vomiting. Get medical attention immediately. Give plenty of water to drink.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse until

pain disappears. Get medical attention if any discomfort continues. Show this Safety Data

Sheet to the medical personnel.

Eye contact Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide

apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after

washing. Show this Safety Data Sheet to the medical personnel.

4.2. Most important symptoms and effects, both acute and delayed

General information The severity of the symptoms described will vary dependent on the concentration and the

length of exposure.

Inhalation May cause irritation.

Ingestion Harmful if swallowed. This product is strongly corrosive. Small amounts may cause serious

damage.

Skin contact This product is strongly corrosive. Causes burns. Prolonged contact causes serious tissue

damage. Harmful in contact with skin. May cause skin sensitisation or allergic reactions in

sensitive individuals.

Eye contact This product is strongly corrosive. Causes severe burns. Causes serious eye damage.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor No specific recommendations. If in doubt, get medical attention promptly.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards Corrosive gases or vapours.

5.3. Advice for firefighters

Protective actions during

firefighting

Keep up-wind to avoid fumes. Avoid breathing fire gases or vapours. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it

out of sewers and watercourses.

Special protective equipment

for firefighters

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective

clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin and eyes. Wear protective clothing as described in Section 8 of this

safety data sheet. Provide adequate ventilation.

6.2. Environmental precautions

Environmental precautions Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled

discharges into watercourses must be reported immediately to the Environmental Agency or

other appropriate regulatory body.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Contain and absorb spillage with sand, earth or other non-combustible material. Collect and

place in suitable waste disposal containers and seal securely. Containers with collected

spillage must be properly labelled with correct contents and hazard symbol.

6.4. Reference to other sections

Wear protective clothing as described in Section 8 of this safety data sheet. Reference to other sections

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid contact with skin and eyes. Mechanical ventilation or local exhaust ventilation may be

required. Do not eat, drink or smoke when using the product. Good personal hygiene

procedures should be implemented.

7.2. Conditions for safe storage, including any incompatibilities

Store at room temperature. Store in tightly-closed, original container. Store away from Storage precautions

incompatible materials (see Section 10).

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

TRIETHYLENETETRAMINE (CAS: 112-24-3)

DNEL Workers - Inhalation; Long term systemic effects: 1 mg/m³

> Workers - Inhalation; Short term systemic effects: 5380 mg/m³ Workers - Dermal; Long term systemic effects: 0.57 mg/kg/day

8.2. Exposure controls

Protective equipment









Appropriate engineering

controls

Provide adequate general and local exhaust ventilation. Observe any occupational exposure limits for the product or ingredients.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles. Personal protective equipment for eye and face protection should comply with European Standard EN166.

Hand protection

To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours. Wear protective gloves made of the following material: Butyl rubber. Nitrile rubber.

Other skin and body

protection

Wear chemical protective suit.

Hygiene measures

Provide eyewash station and safety shower. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke. Change work clothing daily before leaving workplace.

Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Organic vapour filter. Full face mask respirators with replaceable filter cartridges should comply with European Standard EN136. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Dark Grey.

Odour Amine.

Solubility(ies) Soluble in water.

9.2. Other information

Other information Not available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Strong oxidising agents.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Not available.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods

of time.

10.5. Incompatible materials

Materials to avoid Avoid contact with oxidising agents Nitrous acid and other nitrosating agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

Thermal decomposition or combustion products may include the following substances: Nitrous gases (NOx). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide

(CO2). Vapours/gases/fumes of: Ammonia or amines.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

ATE oral (mg/kg) 40,180.0

Acute toxicity - dermal

ATE dermal (mg/kg) 159,675.0

Acute toxicity - inhalation

ATE inhalation (gases ppm) 3,616,201.0

ATE inhalation (vapours mg/l) 884.0

Revision date: 05/04/2018 Revision: 5 Supersedes date: 03/05/2016

CHOCKFAST BLACK HARDENER

ATE inhalation (dusts/mists

mg/l)

1,205.0

Inhalation May cause respiratory irritation.

Ingestion Harmful if swallowed. Small amounts may cause serious damage. This product is strongly

corrosive.

Skin contact May cause serious chemical burns to the skin. Harmful in contact with skin. May cause

sensitisation or allergic reactions in sensitive individuals. May cause skin irritation.

Eye contact This product is strongly corrosive. Contact with concentrated chemical may very rapidly cause

severe eye damage, possibly loss of sight.

Route of entry Inhalation Ingestion Skin and/or eye contact

SECTION 12: Ecological Information

EcotoxicityThe product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment. Avoid releasing into the

environment.

12.1. Toxicity

Toxicity The product contains a substance which is harmful to aquatic organisms and which may

cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

Persistence and degradability There are no data on the degradability of this product.

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

12.4. Mobility in soil

Mobility Not determined.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

Not determined.

12.6. Other adverse effects

Other adverse effects Not determined.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information When handling waste, the safety precautions applying to handling of the product should be

considered.

Disposal methodsDispose of waste to licensed waste disposal site in accordance with the requirements of the

local Waste Disposal Authority.

Waste class 08 04 99

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 2735

UN No. (IMDG) 2735 UN No. (ICAO) 2735 UN No. (ADN) 2735

14.2. UN proper shipping name

Proper shipping name

(ADR/RID)

AMINES, LIQUID, CORROSIVE, N.O.S. (ALIPHATIC AMINE)

Proper shipping name (IMDG) AMINES, LIQUID, CORROSIVE, N.O.S. (ALIPHATIC AMINE)

Proper shipping name (ICAO) AMINES, LIQUID, CORROSIVE, N.O.S. (ALIPHATIC AMINE)

Proper shipping name (ADN) AMINES, LIQUID, CORROSIVE, N.O.S. (ALIPHATIC AMINE)

14.3. Transport hazard class(es)

ADR/RID class 8

ADR/RID classification code C7

ADR/RID label 8

IMDG class 8

ICAO class/division 8

ADN class 8

Transport labels



14.4. Packing group

ADR/RID packing group II

IMDG packing group II

ADN packing group II

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-A, S-B

ADR transport category 2

Emergency Action Code 2X

Hazard Identification Number 80

(ADR/RID)

Tunnel restriction code (E)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16

December 2008 on classification, labelling and packaging of substances and mixtures (as

amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Revision comments Revised formulation.

Revision date 05/04/2018

Revision 5

Supersedes date 03/05/2016

Hazard statements in full H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H332 Harmful if inhaled.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.